

DESCRIPTION

The 3905 Quick Release Valve is installed in a pneumatic system to provide fast exhausting of air from lines, actuators and accumulators. Exhaust air is vented directly from large valve orifices instead of going back through the control valves.

Weight: 1.1 lb. (0.5 kg)

Material: Die cast silicon bronze and stainless steel hardware Operating Temperature: -40°C to +90°C Maximum Operating Pressure: 200 psi (13.8 bar) Pipe Port Size: In and Out ports: ½" NPT Exhaust port: ½" NPT


APPLICATIONS

- Fast release of air applied brakes
- Fast setting of fail safe devices


ORDERING INFORMATION

To order, state model number 3905. A repair kit 3905-RK is available for all seals.


DIMENSIONS AND PARTS LIST



| ITEM | QTY | PART NO. | DESCRIPTION |
|------|-----|-----------|-------------|
| 1 | 1 | 3905-0001 | Valve Body |
| 2 | 1 | 3905-0002 | End Cap |
| 3 | 1 | 3905-0003 | Piston |
| 4 | 1 | 1105-0002 | Diaphragm |
| 5 | 4 | 1001-1008 | Capscrew |
| 6 | 1 | 1201-0014 | Spring |
| 7 | 1 | 1101-0033 | "O" Ring |



SCHEMATIC SYMBOL



MODEL 3905 QUICK RELEASE VALVE ½" NPT