



Stroke

The Model 7033 outboard motor steering cylinder was designed to be attached directly onto the late model outboard motor brackets. The draglink provided is used to connect the cylinder rod onto the motor tiller arm with stainless steel shoulder bolts. The swiveling arrangement between the cylinder and the mounting bracket allows the cylinder to be raised or lowered to suit the height of the tiller arm. The cylinder is of extremely heavy duty construction. Being made entirely of bronze and stainless steel, it will handle 300 horsepower motors with ease.

Since the cylinder bolts directly onto the outboard motor bracket and being supported by the motor, it swivels with the motor when the motor is raised or lowered, thus takes away all the stress on the draglink which now is used primarily to rotate the motor.

This cylinder is ideally suited for all heavy duty outboard motor applications. The standard stroke is 7-1/2". Upon special request, any stroke length is available. The cylinder can also be ordered epoxy-coated.


	Other strokes are available
Working pressure	1000 psi (69 bar)
Effective piston area	1.32 sq. in. (8.5 sq. cm)
Standard Volume	9.9 cu. in. (162 cu. cm)
Piston Rod	3/4" stainless steel hard-
	chromed

7½" (190.5 mm)

Cylinder I.D. 1½" (38.1 mm) Weight 11 lbs. (5 kg)

Model 7033

_	ITEM	QTY	PART NUMBER	DESCRIPTION
_	1	1	7033-0001	Support Bracket
	2	1	7033-0002	End Cap
	3	1	7033-0003	End Cap
	4	1	7033-0004	Drag Link
	5	1	7033-0005	Drag Link Bracket
	6	1	7033-0006	Piston
	7	1	7033-0007	Piston Rod
	8	1	7033-0008L	Shaft Guide, left
	8	1	7033-0008R	Shaft Guide, right
	9	1	7033-0009	Tube
	10	2	7033-0010	Tie Rod
	11	1	7033-0011	Shoulder Bolt
	12	1	7040-0012	Pin
	13	2	7050-0010	Retainer
	14	1	1023-0313	Lock Washer
	15	2	1001-1128	Hex Hd Cap Screw
	16	1	1001-1328	Hex Hd Cap Screw
	17	4	1022-0311	Hex Lock Nut
	18	1	1022-0262	Jam Nut
	19	2	1101-0125	"O" Ring
	20	1	1101-0018	"O" Ring
	21	2	1102-3008	"U" Cup
	22	2	1102-0026	"U" Cup
	23	1	7040-0013	Wear Ring
	24	2	7040-0011	Bleeder Screw
	25	2	1301-0005	Ball 5/32"
	26	1	7033-1011	Shoulder Bolt
	27	1	1022-1312	Lock Nut
	28	4	7033-0015	Spacer
	29	2	7032-0017	Adaptor



All dimensions in inches (mm)

